

AQUAPave®

Permeable On-Site Stormwater Source Control System









Installation Guide:

- 1. Compact and level the sub-base.
- 2. Place the AP SC1000 woven geotex tile with the specified overlap.
- 3. Place and spread the clear crushed open-graded lower Sub-base aggregate without wrinkling or folding the geotextile.
- 4. Compact the lower Sub-base.
- 5. Place and spread the clear crushed open-graded upper Sub-base.
- 6. Compact the clear crushed opengraded upper Sub-base.
- 7. Place the Inbitex® geotextile.
- 8. Place and spread the 5mm clear crush bedding material.
- Compact the 5mm clear crushed open-graded bedding material.
- 10. Loose screed the 5mm clear crush open-graded Bedding Course.
- 11. Place the AquaPave® pavers.
- 12. Compact the AquaPave® pavers.
- 13. Spread and sweep in the AP Engineered Joint Stabilizer.
- 14. Compact the AquaPave® pavers.

Specifications:

ABBOTSFORD CONCRETE PRODUCTS

Pavers are manufactured to ASTM C936/C936M-18 and CSA A231.2-19 specifications.

HydraPressed Slabs to ASTM C1782/C1782M-19 and CSA A231.1-19 specifications.

Concrete strength: 8000 PSI (55 MPA)
Absorption: shall not exceed 5%

Absorption: shall not exceed 5%
Weight: 2-3/8" (60mm): appro

2- ³/₈" (60mm): approx. 28lbs/ft² (140kg/m²) 3- ¹/₈" (80mm): approx. 37lbs/ft² (182kg/m²)

Visit our website at


www.pavingstones.com

for our complete product guide, color selection, design details and photo gallery, or call toll free 1-800-663-4091. The Venetian Cobble Series is one of our most innovative accomplishments to date. Venetian Cobble has the aesthetic appearance of natural cut stone, enhancing the Large Format design motif, while softening the lineal appearance by combining five interrelated shapes.

With our next generation AquaPave System, the Venetian Cobble Series is the first to incorporate our unique spacer bar design. This allows the Venetian Cobble Series to also be installed in sand set applications.



Granite*



Charcoal*



Sandalwood*



Copper Canyon* La Jolla*



*For best results, pavers should be installed from several pallets to ensure color consistency, especially with multi-color blends.







Type 1
228mm x 304mm x 90mm
9" x 12" x 3-9/16"



Type 2
152mm x 304mm x 90mm
6" x 12" x 3-9/16"



Type 3
228 mm x 228mm x 90mm
9" x 9" x 3-9/16"



Type 4

152mm x 228mm x 90mm
6" x 9" x 3-9/16"



Type 5
152mm x 152mm x 90mm
6" x 6" x 3-9/16"

The Venetian Cobble Series comes from the factory in this repeating random pattern that is suitable for machine laying. Machine layable pavers increase efficiency and lowers labor costs.



